



ZIRCON INDUSTRIES, INC.

www.liquidheat.com
www.directchem.com

P.O. Box 22483
Cleveland, Ohio 44122
216/581-7570
FAX 216/581-2868
1-800-547-4328
e-mail: staff@liquidheat.com

APPLICATION GUIDELINES

LATEX 100

LONGEVITY	BLEND RATIOS	COVERAGE (sq ft per blended gal)
One week	1 gal Latex to 100 gal water	40 sq ft
One week	1 gal Latex to 500 gal water	8 sq ft
1-2 months	1 gal Latex to 50 gal water	40 sq ft
1-2 months	1 gal Latex to 250 gal water	8 sq ft
3-4 months	1 gal Latex to 30 gal water	40 sq ft
3-4 months	1 gal Latex to 150 gal water	8 sq ft
6 months	1 gal Latex to 15 gal water	40 sq ft
6 months	1 gal Latex to 75 gal water	8 sq ft
12-18 months	1 gal Latex to 5 gal water	40 sq ft
12-18 months	1 gal Latex to 25 gal water	8 sq ft

*We recommend 1 gal of ZHP water additive per 2,000 gallons Latex blend to be added LAST.

*Blend ratios can be altered by making proper relative square foot coverage adjustment.

*Seal drum after use. Wash out line of sprayer after applying.