

**Contains NO Chlorinated Solvents
(NO 1,1,1-Trichloroethane)**

Sprays as a deep penetrating liquid that flows into areas which are difficult to lubricate. Then, as the solvent carrier evaporates, the liquid forms into a grease that is resistant to high temperature and pressure.

After setting up, the grease will not wash away with water or steam and will resist water throwoff and heavy shock load. Withstands acid, salt spray and oxidation.

USE ON: Wire rope, open gears, linkages, draglines, fittings, winches, cranes, cams, valves, cables, hoists, pulleys and rollers.

DIRECTIONS: Spray first spray up close to flush off old grease and dirt build up. Then spray a thin film on surface to be lubricated. Liquid will creep and penetrate then gel in approximately 20 minutes.

DANGER: Contains Isoparaffinic Hydrocarbon (64741-66-8), Liquefied Petroleum Gas (68476-85-7) and Lithium Grease (N/A). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

KEEP OUT OF REACH OF CHILDREN

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

HMIS RATING: Health, 1; Flammability, 3; Reactivity, 0; Personal Protection B.

KEEP OUT OF REACH OF CHILDREN

For further information consult Material Safety Data Sheet.



ZIRCON INDUSTRIES, INC.

P.O. BOX 22483
CLEVELAND, OH 44122
PHONE (216) 581-7570

**ZIRCON
INDUSTRIES
INC.**



RED LUBE

HIGH TEMP RED SPRAY GREASE

- Lubricates and Rust Proofs
- Air Cures to Resistant Grease

**LITHIUM BASE
TEMPERATURE AND
PRESSURE RESISTANT**

NET WT. 11 OZ. (311 Grams)

DANGER:
EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
VAPOR HARMFUL. CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.