

An excellent anti-friction and anti-seize lubricant containing micron-sized graphite.

Suitable for temperatures from - 110°F to 600° and pressures to 100,000 psi.

Inert to water, oil alkalis and many acids
- will not attract dust.

For assembly and run-in on engine components, maintenance on ovens and conveyors, gaskets and stop off coating, wire drawing, rubber mold release, etc.

DIRECTIONS

1. SHAKE VIGOROUSLY BEFORE EACH USE.
2. Clean and dry surface to be sprayed.
3. Hold can about 8 to 10 inches from surface.

FOR INDUSTRIAL USE ONLY

Non-Grease Lubricant for Autorack Equipment
AAR Specification M-971-93
Name of Manufacturer: **ZIRCON INDUSTRIES, INC.**
Amount of Lubricant in the Container:

Date of Manufacture:
Batch No.:

ZIRCON DRI-GRAPHITE Micro-Film LUBRICANT

**ZIRCON
INDUSTRIES
INC.**

P.O. Box 22483
Cleveland, Ohio 44122
216/581-7570



INDUSTRIAL-COMMERCIAL
MAINTENANCE MATERIALS

KEEP OUT OF REACH OF CHILDREN

Recommended especially for chain drives, sprockets, open gears, pinions, cables, lathe bed and rails and reduction of friction where greaseless lubrication is needed. Advantages of Dri-Graphite Lubrication:

Better application - chemically attracted to metal.

No build-up of excess material.

Resists adhesion of dirt and foreign particles.

Staying quality. Reduces frequency of lubrication.

Better lubrication reduces wear.

Withstands higher operating temperatures.

IMPORTANT - For best results apply to pre-cleaned and dried surfaces.

CAUTION:

CONTAINS: Alcohol. Use with adequate ventilation. Avoid breathing of vapor. If swallowed, induce vomiting, call physician. In case of eye contact, flush eye repeatedly with water. Call physician immediately. Keep away from flames.

KEEP OUT OF REACH OF CHILDREN

**FAST DRY
STRONG BOND
OIL FREE**