



ZIRCON INDUSTRIES, INC.

www.liquidheat.com

SAFETY DATA SHEET

GHS FORMAT

1. IDENTIFICATION

PRODUCT NAME	Z99 Safety Solvent BULK
SYNONYMS	Degreaser
RECOMMENDED USE/RESTRICTIONS	For industrial use only
MANUFACTURER	Zircon Industries, Inc. 4920 Commerce Parkway Cleveland OH 44128 Phone: (216) 595-0200 Fax: (216) 595-0202 Email: zircon2@sbcglobal.net
EMERGENCY PHONE NUMBER	INFOTRAC (800) 535-5053

2. HAZARDS IDENTIFICATION

HAZARD DESIGNATION	None
---------------------------	------

GHS CLASSIFICATION:

HEALTH	ENVIRONMENTAL	PHYSICAL
Acute toxicity - Oral, Category 5 Carcinogenicity - Category 2		

GHS LABEL:



Health Hazard

WARNING

H351: Suspected of causing cancer

H303: May be harmful if swallowed

PRECAUTIONARY STATEMENT(S)

PREVENTION:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P281: Use personal protective equipment as required.

SAFETY DATA SHEET

GHS FORMAT

P280: Wear protective gloves/eye protection/face protection
RESPONSE:
P308 + P313: IF exposed or concerned: Get medical advice/attention. P312: Call a POISON CENTER/doctor/physician if you feel unwell.
STORAGE:
P405: Store locked up. P403 + P235: Store in a well-ventilated place. Keep cool.
DISPOSAL:
P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	WEIGHT %	CAS
Distillates (petroleum), hydrotreated light	45-60%%	64742-47-8
Tetrachloroethylene	50-65%	127-18-4

4. FIRST AID MEASURES

EYES	Flush eyes with water for 15 minutes. Get medical attention.
SKIN	Wash with soap and water. Get medical attention if irritation develops or persists.
INGESTION	Immediately drink two glasses of water or milk. Do not induce vomiting. Get medical attention.
INHAILATION	Remove victim to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:	SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO ₂ , water spray or fire fighting foam. LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire exposed containers. Keep containers and surroundings cool with water spray.
FIRE FIGHTING PROCEDURES:	

SAFETY DATA SHEET

GHS FORMAT

	Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam. Exposure to decomposition products may be a hazard to health. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None
COMBUSTION PRODUCTS:	None

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL:	Absorb liquid and place in sealed container for disposal.
LARGE SPILL:	Absorb liquid and place in sealed container for disposal. Avoid runoff into storm sewers and ditches which lead to waterways. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust.
ENVIRONMENTAL PRECAUTIONS	
WATER SPILL:	Keep material out of storm sewers and ditches that lead to waterways.
LAND SPILL:	Spills and releases may have to be reported to federal and/or local authorities.
AIR SPILL:	Control or stop the loss of materials to the atmosphere.
SPECIAL PROTECTIVE EQUIPMENT:	Wear suitable protective clothing, gloves and eye/face protection.

7. HANDLING AND STORAGE

HANDLING:	Do not get in eyes, on skin or on clothing. Keep container closed. Use only with adequate ventilation. Use good personal hygiene practices. Wash hands before eating, drinking,
------------------	---

SAFETY DATA SHEET

GHS FORMAT

	smoking. Remove contaminated clothing and clean before re-use. Destroy contaminated belts and shoes and other items that cannot be decontaminated. Keep operating temperatures below ignition temperatures at all times.
STORAGE:	Store in tightly closed containers in cool, dry, well-ventilated area away from incompatibles. Store at ambient or lower temperature. Store out of direct sunlight. Keep containers tightly closed and upright when not in use. Protect against physical damage. Do not cut, grind, drill, or weld on or near containers unless precautions are taken against these hazards.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS			
Component	OHSA		ACGIH
	PEL	STEL	TLV
Distillates (petroleum), hydrotreated light	200ppm		200ppm
Tetrachloroethylene	100ppm		100ppm

ENGINEERING CONTROLS | Use only in a well ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE:	Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).
SKIN:	Wear chemical resistant neoprene, butyl rubber or vinyl gloves.
RESPIRATORY:	NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
PROTECTIVE CLOTHING:	Wear protective gloves and clean body-covering clothing. Chemically resistant clothing and boots may be required.
WORK HYGIENIC PRACTICES	Establish good personal hygiene and work practices. Always wash hands and face before eating, drinking or smoking. Provide safety shower and eye wash station in work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

GHS FORMAT

PHYSICAL STATE:	Liquid
ODOR:	Mild hydrocarbon
APPEARANCE:	Clear, colorless liquid
pH:	Neutral
PERCENT VOLITILE:	100%
VAPOR PRESSURE:	8.45mmHg
VAPOR DENSITY:	4.55
BOILING POINT:	266°F
FREEZING POINT:	-85°F
FLASHPOINT AND METHOD:	142°F (TCC)
SOULUBILITY IN WATER:	None
EVAPORATION RATE:	0.1
SPECIFIC GRAVITY:	1.083
VISCOSITY:	<1 Centipoise

NOTE: The information in this section is calculated from specific known information about this product. This information should not be used as exact test results or specifications. The information is provided as typical properties for this product.

10. STABILITY AND REACTIVITY

STABLE:	Yes
HZARDOUS POLYMERIZATION:	No
STABILTY:	Stable under ordinary conditions of use and storage.
CONDITIONS TO AVOID:	None
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon dioxide and/or carbon monoxide
INCOMPATIBLE MATERIALS:	Strong oxidizing agents

11. TOXICOLOGICAL INFORMATION

ACUTE	
DERMAL LD₅₀:	Not indicated
ORAL LD₅₀:	Not indicated
INHALATION LC₅₀:	Not indicated
EYE EFFECTS:	Mildly irritating to eyes.
SKIN EFFECTS:	May be absorbed through the skin in harmful amounts.
CARCINOGENINITY	
IARC:	Not listed
NTP:	Not listed

SAFETY DATA SHEET

GHS FORMAT

OHSA:	Not listed
REPRODUCTIVE EFFECTS:	Not indicated
TERATOGENIC EFFECTS:	No data available
MUTAGENICITY:	Not indicated

16. OTHER INFORMATION**HMIS RATINGS:**

2
2

REACTIVITY 0PERSONAL PROTECTION **LAST REVISED:** 2/18/18

Disclaimer: The information contained herein is accurate to the best of our knowledge. Zircon Industries, Inc. makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances.

**ZIRCON INDUSTRIES, INC.**

(800) 547-4328